

# AVE-215ECO

LED HD HDMI Monitor



AMERICAN VIDEO EQUIPMENT

## AVE-215ECO

<b>Panel Type</b>	(16:9) LED Monitor
<b>Case Type</b>	Plastic
<b>Maximum Resolution</b>	1920 (H) x 1080 (V)
<b>MTBF</b>	30,000 hrs
<b>Active Display Area</b>	476.64 (H) x 268.11 (V) mm
<b>Pixel Pitch</b>	0.24825 (H) x 0.24825 (V) mm
<b>Bezel Thickness</b>	Left/Right 15mm U/D 16mm
<b>Contrast Ratio</b>	1000 : 1
<b>Brightness</b>	250 cd/m <sup>2</sup>
<b>Response Time</b>	5m.sec
<b>Viewing Angle</b>	85/85/80/80°
<b>Display Colours</b>	16.7 M
<b>Video Synchronisation</b>	Yes
<b>PC Compatibility</b>	Yes
<b>Aspect Ratio</b>	16:9
<b>VGA Auto Frequency Correction</b>	Yes
<b>Speakers</b>	N/A
<b>Sound Demodulation</b>	N/A
<b>Mute</b>	N/A
<b>Work Humidity</b>	5% - 90%
<b>Work Temperature</b>	-10 - +50°C
<b>Volume +/- Power On/Off</b>	Yes



## IN / OUT INTERFACE

<b>Video Interface</b>	HDMI, VGA
<b>Audio</b>	N/A
<b>Power Interface</b>	DC 2.1mm
<b>Certification</b>	CE, ROHS, FCC
<b>VESA</b>	100 x 100mm
<b>Stand Type</b>	Table Stand
<b>Colour</b>	Black
<b>Button Position</b>	Bottom right
<b>Packing Dimensions</b>	548mm x 406mm x 96mm
<b>Nett Weight</b>	3.1 Kgs
<b>Gross Weight</b>	4.1 Kgs

## POWER

<b>Power Supply</b>	DC
<b>Voltage</b>	DC 12V 2A
<b>Power Consumption</b>	20 Watt

## OSD CONTROLS

Brightness, Contrast, Eco, DCR, H.Position, V. Position, Clock, Phase, Aspect, Color Temp, OSD setting, OSD language, OSD H. Pos, OSD V. Pos, OSD timer, OSD Transparency, Factory Reset, Signal Source, Volume

## OSD LANGUAGE

English, Italian, German, Spanish, French, Russian, Polish, Danish

## ACCESSORIES

Power cord, Adapter, Stand, User's guide, HDMI cable

# AVE-215ECO

LED HD HDMI Monitor

