

AVE-236FHD

LED Monitor



AMERICAN VIDEO EQUIPMENT

AVE-236FHD

Panel Type	(16:9) LED Monitor
Case Type	Plastic
Maximum Resolution	1920 (H) x 1080 (V)
MTBF	50,000 hrs
Active Display Area	521.28 (H) x 293.22 (V) mm
Pixel Pitch	0.2715 (H) x 0.2715 (V) mm
Bezel Thickness	L/R: 16.6 mm, U: 18mm, D:23.9 mm
Contrast Ratio	1000 : 1
Brightness	250 cd / m2
Response Time	5m.sec (G to G)
Viewing Angle	85 / 85 U / D 75 / 75°
Display Colours	16.7 M
Video Synchronisation	Yes
PC Compatibility	30-80 KHz (H) / 56-75Hz (V)
Aspect Ratio	16:9
VGA Auto Frequency Correction	Yes
Speakers	2 * 3W
Sound Demodulation	Stereo
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	-10 - +50 °C
Volume +/- Power On/Off	Yes



IN / OUT INTERFACE

Video Interface	CVBS BNC in x1 / out x1, VGA in x 1, HDMI in x 1
Audio	PC Audio in x 1
Termination	75 ohm
Certification	CE, FCC, ROHS, REACH, WEEE
VESA	100 x 100
Stand Type	Desk
Colour	Black
Button Position	Bottom right, front of case
Packing Dimensions	625mm x 120mm x 450mm
Nett Weight	4.7 Kgs
Gross Weight	5.8 Kgs

POWER

Power Supply	12v DC 3 Amp
Power Consumption	28 Watt
Voltage	100 - 240v AC
	50 - 60Hz
Power Interface	DC 12V in 2.1mm x 1

OSD CONTROLS

Picture	Colour, brightness, contrast ratio, aspect ratio etc.
PC (VGA only)	OSD position
Audio	Bass, Treble, Balance etc.
Settings	Language, Default settings, Prevent Burn In, OSD time etc.

OSD LANGUAGE

English, French, German, Polish, Italian, Spanish, Danish, Dutch

ACCESSORIES

HDMI Cable, User Manual, Power Adapter
Kettle lead, Remote control, Screws, Table Stand

AVE-236FHD

LED Monitor

